



Munich Personal RePEc Archive

Cooperative games for minimum cost spanning tree problems

Bergantiños, Gustavo and Vidal-Puga, Juan

Universidade de Vigo

22 December 2020

Online at <https://mpra.ub.uni-muenchen.de/104911/>
MPRA Paper No. 104911, posted 23 Dec 2020 15:05 UTC

Cooperative games for minimum cost spanning tree problems*

Gustavo Bergantiños

Juan Vidal-Puga

Universidade de Vigo

Universidade de Vigo

December 22, 2020

Abstract

Minimum cost spanning tree problems are well known problems in the Operations Research literature. Some agents, located at different geographical places, want a service provided by a common supplier. Agents will be served through costly connections. Some part of the literature has focused, mainly, in studying how to allocate the connection cost among the agents. We review the papers that have addressed the allocation problem using cooperative game theory.

Keywords: minimum cost spanning tree problems, cooperative games, core, Shapley value.

1 Introduction

Several problems involving network formation have been studied in operations research and economics. The operations research literature is more focused in efficient algorithm designs and computational complexity. The economic literature focuses on aspects such as cost sharing within networks. In this paper we focus on the cost sharing aspect. Hence, this review belongs to the well-known literature of cost allocation.

In this paper, we consider *minimum cost spanning tree problems*, briefly *mcstp*. A group of agents, which are located at different geographical places, want a particular service which can only be provided by a common supplier, called the source. Agents will

*We gratefully acknowledge the comments made by Y. Chun and C. Trudeau. Our work is partially supported by research grant ECO2017-82241-R from *Ministerio de Economía y Competitividad*, and ED431B 2019/34 from *Xunta de Galicia*.

be served through costly connections. Agents are indifferent between being connected directly or indirectly to the source. There are many situations that can be modeled in this way. For instance, several towns may draw power from a common power plant, and hence have to share the cost of the distribution network (Dutta and Kar, 2004). Bergantiños and Lorenzo (2004, 2005, 2008) study a real situation where villagers had to pay the cost of constructing pipes from their respective houses to a water supplier. Other examples include communication networks, such as telephone, Internet, or cable television.

The literature on *mcstp* starts by defining algorithms for constructing *minimal (cost spanning) trees* (*mt* for short). We can mention, for instance, the papers of Borůvka (1926); Kruskal (1956); Prim (1957). However, constructing an *mt* is only part of the problem. Another important issue is how to allocate the cost associated with *mt* among agents. Claus and Kleitman (1973) were the first to address the cost sharing aspect, and Bird (1976) proposed a rule, now known as the Bird’s rule, through Prim’s algorithm. Bird (1976) also associated a cooperative game with any *mcstp*. He proved that this rule belongs to the core of the cooperative game. Many papers have followed addressing the cost allocation problem arising from *mcstp*. Early works and reviews are due to Aarts (1994); Feltkamp (1995); Curiel (1997); Borm et al. (2001). Trudeau (2013) reviews some cost sharing rules focusing on two rules (to be addressed below): the folk rule and the Kar’s rule, comparing several axiomatic characterizations. Trudeau and Vidal-Puga (2019) review the main axiomatic characterizations of the rules based on the Shapley value in *mcstp*.

There are two possible ways for defining rules in *mcstp*. The first way is the direct approach, which defines rules directly from the structure of the problem. In this review, we revise rules that are defined through the algorithms for computing the *mt* defined above (namely, Boruvka, Prim, and Kruskal). The idea of such rules is as follows: the algorithm selects the arc, and the rule decides how to divide its cost between the agents. Each agent pays the sum of the assigned costs over all selected arcs by the algorithm.

We also review the rules that are defined through a cone-wise decomposition. Each *mcstp* can be decomposed as a linear combination of the so called *elementary problems*, where each cost is either 0 or 1. The rule states how to divide the cost of each elementary problem between the agents. Each agent pays the sum of the assigned costs over all elementary problems.

The second way is an indirect approach through cooperative games. First, we associate with each problem a cooperative game. Second, we compute a solution for cooperative

games (Shapley value, core, ...) in the associated cooperative game. Third, we define the rule in the original problem as the solution applied to the cooperative game associated with the original problem. This indirect approach is quite standard and has been considered in many economic problems. Some classical examples are the airport problem (Littlechild and Owen, 1973), where the cost of a runway has to be divided among different airplanes, and bankruptcy problems (O'Neill, 1982; Aumann and Maschler, 1985) where an estate should be divided among several claimants. Other recent examples are the museum pass problem (Ginsburgh and Zang, 2003; Bergantiños and Moreno-Ternero, 2015), where the revenue generated by the sale of museum cards has to be divided among the museums, and the broadcasting problem (Bergantiños and Moreno-Ternero, 2020), where the revenues from broadcasting sport league events must be divided among the teams.

In this second approach, the most studied case in the literature is the case of private nodes. It is assumed that, when computing the value of a coalition, agents in such coalition can use only the nodes of such coalition. However, there are other possible approaches, as for example the case of public nodes, where it is assumed that agents in a coalition can use nodes outside the coalition.

So far, there have been up to five cooperative games in the literature of *mcstp*: the private game, the irreducible game, the optimistic game, the public game, and the cycle-complete game.

Private game Bird (1976) associates with each *mcstp* a cooperative game with transferable utility where the worth of each coalition S is computed assuming that agents in $N \setminus S$ are not participating. It is a pessimistic approach because agents in $N \setminus S$ are supposed not to cooperate. The private assumption makes their nodes unavailable.

Irreducible game Given an *mcstp* (N_0, C) , Bird (1976) defines the irreducible associated problem (N_0, C^*) . The idea is to reduce the costs of C as much as possible without reducing the cost of the minimal tree of C . The irreducible game associated to a *mcstp* (N_0, C) is the private game associated to the irreducible problem (N_0, C^*) .

Optimistic game Bergantiños and Vidal-Puga (2007b) associate with each *mcstp* a cooperative game with transferable utility where the cost of each coalition S is computed assuming that agents in $N \setminus S$ are already connected. This game is called optimistic because agents in $N \setminus S$ are already connected to the source and agents in S can connect to the source through agents in $N \setminus S$ for free.

Public game Bogomolnaia and Moulin (2010) were the first to formally consider the case where the cost of each coalition S is computed assuming that, even though agents in $N \setminus S$ are not connected to the source, agents in S can connect to the source through agents in $N \setminus S$ by paying the costs of the arcs they use.

Cycle-complete game Given an *mcstp* (N_0, C) , Trudeau (2012) defines the associated cycle-complete problem (N_0, C^{**}) . The idea is to achieve concavity by reducing the costs of C as much as possible without reducing the cost of any minimal cycle. The cycle-complete game associated to a *mcstp* (N_0, C) is the private game associated to the cycle-complete problem (N_0, C^{**}) .

The most studied solutions in the five cooperative games we review are the core and the Shapley value. Nevertheless, some other solutions, for instance the nucleolus (Schmeidler, 1969) and weighted Shapley values (Shapley, 1953a; Kalai and Samet, 1987), have also been considered. We have tried to be exhaustive and to mention all papers studying deeply some aspect of the five cooperatives games.

The paper is organized as follows. In Section 2, we introduce *mcstp* and cooperative games with transferable utility. In Section 3, we review the results obtained for the private game. In Section 4, we review the results obtained for the irreducible game. In Section 5, we review the results obtained for the optimistic game. In Section 6, we review the public game. In Section 7, we review the results obtained for the cycle-complete game. In Section 8, we study the relation between the cores of these games. In Section 9, we conclude.

2 Preliminaries

In this section we formally define minimum cost spanning tree problems and cooperative games.

Let $\mathbb{N}_+ = \{1, 2, \dots\}$ be the set of possible agents (nodes). We denote by N a general finite subset of \mathbb{N}_+ , usually assumed to be $N = \{1, \dots, n\}$.

Given a non-empty, finite subset $N \subset \mathbb{N}_+$, let Π_N denote the set of all orders in N . Given $\pi \in \Pi_N$, let $Pre(i, \pi)$ denote the set of nodes in N which come before node i in the order given by π , i.e.,

$$Pre(i, \pi) = \{j \in N \mid \pi(j) < \pi(i)\}.$$

For notational simplicity, given $\pi \in \Pi_N$, we denote node $i \in N$ with $\pi(i) = s$ as π_s .

Moreover, given $\pi \in \Pi_N$ and $S \subset N$, let π_S denote the order induce by π among agents in S .

For each non-empty, finite $N \subset \mathbb{N}_+$, let $\Delta(N) = \{x \in \mathbb{R}_+^N : \sum_{i \in N} x_i = 1\}$.

2.1 Minimum cost spanning tree problems

We consider networks whose nodes are elements of a set $N_0 = N \cup \{0\}$, where $N \subset \mathbb{N}_+$ is non-empty and finite, and 0 is a special node called the *source*.

A *cost matrix* $C = (c_{ij})_{i,j \in N_0}$ represents the cost of direct link between any pair of nodes. We assume that $c_{ij} = c_{ji} \geq 0$ for each $i, j \in N_0$ and $c_{ii} = 0$ for each $i \in N_0$. Since, $c_{ij} = c_{ji}$ we work with undirected arcs, i.e., $(i, j) = (j, i)$.

We denote the set of all cost matrices over N as \mathcal{C}^N . Given $C, C' \in \mathcal{C}^N$, we say $C \leq C'$ if $c_{ij} \leq c'_{ij}$ for all $i, j \in N_0$.

A *minimum cost spanning tree problem*, briefly an *mcstp*, is a pair (N_0, C) where $N \subset \mathbb{N}_+$ is a finite set of agents, 0 is the source, and $C \in \mathcal{C}^N$ is the cost matrix.

Given an *mcstp* (N_0, C) , we define the *mcstp* induced by C for $S \subset N$ as (S_0, C) .

A *network* g over N_0 is a subset of $\{(i, j) : i, j \in N_0\}$. The elements of g are called *arcs*.

Given a network g and a pair of nodes i and j , a *path* from i to j in g is a sequence of different arcs $\{(i_{h-1}, i_h)\}_{h=1}^l$ satisfying $(i_{h-1}, i_h) \in g$ for all $h \in \{1, 2, \dots, l\}$, $i = i_0$, and $j = i_l$. A *cycle* is a path from i to i in g with $i \in N_0$ and at least two different arcs.

Let \mathcal{G}^N denote the set of all networks over N_0 , and let \mathcal{G}_0^N denote the set of all networks where every agent $i \in N$ is connected to the source, i.e., there exists a path from agent i to the source.

Given a network $g \in \mathcal{G}^N$, let $P(g) = \{S_k(g)\}_{k=1}^{n(g)}$ denote the partition of N_0 in connected components induced by g . Formally, $P(g)$ is the only partition of N_0 satisfying the following two properties:

1. If $i, j \in S_k(g)$, then agent i and agent j are connected in g .
2. If $i \in S_k(g)$, $j \in S_l(g)$ and $k \neq l$, then agent i and agent j are not connected in g .

Given a network $g \in \mathcal{G}^N$ and $i \in N_0$, let $S(P(g), i)$ denote the set in $P(g)$ to which agent i belongs to.

Given an *mcstp* (N_0, C) and $g \in \mathcal{G}^N$, we define the *cost* associated with g as

$$c(N_0, C, g) = \sum_{(i,j) \in g} c_{ij}.$$

When there is no ambiguity, we write $c(g)$ or $c(C, g)$ instead of $c(N_0, C, g)$.

A *spanning tree* is a network such that for all $i \in N$ there is a unique path from agent i to the source. A *minimal tree* for (N_0, C) , briefly an *mt*, is a spanning tree t^* over N_0 such that

$$c(t^*) = \min_{g \in \mathcal{G}_0^N} c(g).$$

It is well-known that an *mt* exists, even though it is not necessarily unique. Borůvka (1926); Kruskal (1956); Prim (1957) provide algorithms for computing an *mt*. Given an *mcstp* (N_0, C) , we denote the cost associated with any *mt* for (N_0, C) as $m(N_0, C)$.

Given an *mcstp* (N_0, C) and an *mt* t^* , Bird (1976) defines the *minimal network* (N_0, C^{t^*}) associated with t^* as follows: $c_{ij}^{t^*} = \max_{(k,l) \in g_{ij}^*} \{c_{kl}\}$, where g_{ij}^* denotes the unique path in t^* from agent i to agent j . It is well known that C^{t^*} is independent from the chosen t^* . Hence, we can define the *irreducible form* (N_0, C^*) of an *mcstp* (N_0, C) as the minimal network (N_0, C^{t^*}) associated with any *mt* t^* .

Given an *mcstp* (N_0, C) , Trudeau (2012) defines the *cycle-complete network* (N_0, C^{**}) as follows: $c_{ij}^{**} = \max_{(k,l) \in g_{ij}^{**}} \{c_{kl}\}$, where g_{ij}^{**} denotes the cycle with minimal cost containing both agent i and agent j . It is clear that $c_{ij}^{**} = c_{ij}$ whereas (i, j) belongs to a cycle with minimal cost (among those containing both agent i and agent j), and hence C^{**} is independent of the criterion used to chosen minimal cycles, in case there are more than one.

Next example illustrates some of the concepts introduced above.

Example 2.1 *Figure 1(a) depicts a minimum cost spanning tree problem. There are three agents 1, 2, and 3. The source is denoted by 0. These nodes are represented by circles, where the connection between them are represented by straight lines. Numbers by the lines represent the cost of each connection. The minimal tree is $\{(0, 1), (1, 2), (1, 3)\}$. The irreducible form (b) and the cycle-complete network (c) are also depicted.*

A (*cost sharing*) *rule* is a function f such that $f(N_0, C) \in \mathbb{R}^N$ and $\sum_{i \in N} f_i(N_0, C) = m(N_0, C)$ for each *mcstp* (N_0, C) . As usual, $f_i(N_0, C)$ represents the cost assigned to agent i .

2.2 Rules defined through the problem

In this subsection we mention some rules of the literature that are defined directly through the problem, without using cooperative games.

We first consider rules defined through algorithms for computing an *mt*. The idea is as follows. The algorithm selects the arc we construct and the rule decides how the cost




Figure 1: Example of a *mcstp* (a) and its irreducible (b) and cycle-complete (c) forms.

of the selected arc is divided between the agents. Finally, each agent pays the sum of the costs over the arcs selected by the algorithm.

We also consider rules that are defined through a cone-wise decomposition. The idea is as follows. We first decompose the original problem as the sum of simpler problems. We solve these simpler problems. The solution to the original problem is obtained by adding the solutions to the simpler problems.

Rules defined through Prim's algorithm

Prim (1957) provides an algorithm for computing a minimal tree. The idea is as follows. Starting from the source, we sequentially add arcs with the lowest cost and without introducing cycles. We now introduce two rules based on Prim's algorithm.

The *Bird's rule*, denoted as $B(N_0, C)$, was introduced by Bird (1976) in *mcstp* with a unique *mt*, and further studied in Granot and Huberman (1981); Feltkamp et al. (2000); Gómez-Rúa and Vidal-Puga (2011). The idea is the following. Agents connect sequentially to the source paying their connection cost. Let (N_0, C) be an *mcstp* with a unique *mt*, denoted by t^* . Given $i \in N$, let i^0 be the first node in the unique path in t^* from agent i to the source. Then, for each $i \in N$, we define

$$B_i(N_0, C) = c_{i^0 i}.$$

Later on, Dutta and Kar (2004) extend this definition for any *mcstp* as an average of the trees associated with Prim's algorithm. Given $\pi \in \Pi_N$, they defined $B^\pi(N_0, C)$ as the allocation obtained when applied the previous protocol to (N_0, C) and solved the indifferences by selecting the first agent given by π . Then they defined

$$B(N_0, C) = \frac{1}{n!} \sum_{\pi \in \Pi_N} B^\pi(N_0, C).$$

Chun and Lee (2012) introduce the family of *sequential contributions rules* for *mcstp* with a unique *mt*. The connection cost of each agent is paid by this agent and the agents that connect to the source through this agent. Notice that the Bird's rule is a member of this family.

The *Dutta-Kar's rule*, denoted as $DK(N_0, C)$, was introduced by Dutta and Kar (2004). It is also defined through Prim's algorithm. Let (N_0, C) be an *mcstp* with a unique *mt*. Assume that agents connect to the source via Prim's algorithm, but with a pivotal switch in the allocation cost at each step. When there are more than one *mt*, they define a rule DK^π for each $\pi \in \Pi_N$, obtained by selecting the first agent given by π . See Dutta and Kar (2004) for a formal definition.

Dutta and Kar (2004) extend this definition for any *mcstp* similarly to the Bird's rule. Namely,

$$DK(N_0, C) = \frac{1}{n!} \sum_{\pi \in \Pi_N} DK^\pi(N_0, C).$$

Rules defined through Kruskal's algorithm

Kruskal (1956) defines another algorithm for computing an *mt*. The *mt* is constructed by sequentially adding arcs with the lowest cost without introducing cycles.

Formally, we start with $A^0(C) = \{(i, j) \mid i, j \in N_0, i \neq j\}$ and $g^0(C) = \emptyset$.

Stage 1: Take an arc $(i^1(C), j^1(C)) \in A^0(C)$ such that $c_{i^1(C)j^1(C)} = \min_{(i,j) \in A^0(C)} \{c_{ij}\}$. If there are several arcs satisfying this condition, select one of them. We then update $A^1(C) = A^0(C) \setminus \{(i^1(C), j^1(C))\}$, and $g^1(C) = \{(i^1(C), j^1(C))\}$.

Stage $p + 1$: Given $A^p(C)$ and $g^p(C)$, consider an arc $(i, j) \in A^p(C)$ such that $c_{ij} = \min_{(k,l) \in A^p(C)} \{c_{kl}\}$. If there are several arcs satisfying this condition, select one of them. Two cases are possible:

1. If $g^p(C) \cup \{(i, j)\}$ has a cycle, then repeat Stage $p + 1$ with $A^p(C) \setminus \{(i, j)\}$ instead of $A^p(C)$ and the same $g^p(C)$.
2. If $g^p(C) \cup \{(i, j)\}$ has no cycles, then take $(i^{p+1}(C), j^{p+1}(C)) = (i, j)$, $A^{p+1}(C) = A^p(C) \setminus \{(i, j)\}$, and $g^{p+1}(C) = g^p(C) \cup \{(i, j)\}$.

This process is completed in $|N|$ stages. Let $g^{|N|}(C)$ be the tree obtained following Kruskal's algorithm. This algorithm leads to a tree, which is not always unique. When no confusion arises, we write A^p , g^p , and (i^p, j^p) instead of $A^p(C)$, $g^p(C)$, and $(i^p(C), j^p(C))$.

Norde et al. (2004) present a subtraction algorithm, closely related to Kruskal's, for the determination of minimum cost spanning trees.

Bergantiños et al. (2010, 2011) consider a family of rules through Kruskal's algorithm. At each step of the algorithm, an arc is added to the network. The cost of the arc is divided between the agents according with a function ϱ specifying the part of the cost paid by each agent. Each agent pays the sum of the costs of the arcs selected by Kruskal's algorithm.

We now introduce this family formally.

Let $\mathcal{P}(N_0)$ denote the set of all partitions over N_0 . Let $P = \{S_0, S_1, \dots, S_m\}$ be a generic element of $\mathcal{P}(N_0)$ such that $0 \in S_0$. We assume that for all $k = 0, \dots, m$, $S_k \neq \emptyset$. Given $P, P' \in \mathcal{P}(N_0)$, we say that P is 1-finer than P' if P' is obtained from P by merging two elements of P .

A sharing function ϱ associates with each pair of partitions (P, P') , where P is 1-finer than P' , a vector $\varrho(P, P') \in \Delta(N)$ satisfying the following path independence condition (see Bergantiños et al. (2010) for the definition of this condition). For each sharing function ϱ , we define the rule f^ϱ as follows. Given an *mcstp* (N_0, C) and $i \in N$, we define

$$f_i^\varrho(N_0, C) = \sum_{p=1}^{|N|} c_{ip} \cdot \varrho_i(P(g^{p-1}), P(g^p)).$$

These functions are called *Kruskal's sharing rules*. We now consider some rules and a family of rules in the literature which are members of the the family of Kruskal's sharing rules.

Obligation rules, introduced by Tijs et al. (2006a), are defined through obligation functions, that specify the obligation of each agent in each coalition.

An obligation function for N is a map o that assigns to each $S \in 2^{N_0} \setminus \{\emptyset\}$ a vector $o(S) \in \mathbb{R}^S$ satisfying the following three conditions:

- For each $S \in 2^{N_0} \setminus \{\emptyset\}$ such that $0 \notin S$, $o(S) \in \Delta(S)$.
- For each $S \in 2^{N_0} \setminus \{\emptyset\}$ such that $0 \in S$, $o_i(S) = 0$ for each $i \in S$.
- For each $S, T \in 2^{N_0} \setminus \{\emptyset\}$ with $S \subset T$ and $i \in S$, $o_i(S) \geq o_i(T)$.

Given an obligation function o we can define the Kruskal sharing rule f^{o° where for each $i \in N$,

$$\varrho_i(P(g^{p-1}), P(g^p)) = o_i(S(P(g^{p-1}), i)) - o_i(S(P(g^p), i)).$$

Bergantiños et al. (2011) prove that the set of obligation rules is given by

$$\{f^{o^\circ}(N_0, C) : o \text{ is an obligation function}\}.$$

We now introduce some distinguished elements of the family of obligation rules.

The *folk rule*, denoted by $F(N_0, C)$, was firstly considered in Feltkamp et al. (1994). It can be seen as a Kruskal sharing rule where ϱ satisfies the following principles:

- Only agents who benefit directly when adding an arc pay for that arc.
- All agents in the same group pay the same.
- The total amount paid by a group is proportional to the new agents to whom this group is connected.

Formally, the folk rule corresponds with the obligation function o where for each $S \subset N$ and each $i \in S$,

$$o_i(S) = \frac{1}{|S|}.$$

The folk rule is, probably, the most studied rule in this literature. It can be defined in several ways, different from the Kruskal's algorithm approach considered above. Besides, it has also been studied thorough the axiomatic approach and the non-cooperative approach. Some papers studying the folk rule are Branzei et al. (2004); Bergantiños and Vidal-Puga (2009, 2010); Ciftei and Tijis (2009); Bergantiños et al. (2014); Subiza et al. (2016); Norde (2019); Giménez-Gómez et al. (2020); Hernández et al. (2020).

Optimistic weighted Shapley rules are introduced in Bergantiños and Lorenzo-Freire (2008b,a). Each agent i has a weight $w_i > 0$. The sharing function ϱ is defined proportionally to such weights. Formally, for each weight system $w = (w_i)_{i \in N}$, the optimistic weighted Shapley rule $f^{\varrho^{ow}}$ is the Kruskal sharing rule associated with the obligation function o where for each $S \subset N$ and each $i \in S$,

$$o_i(S) = \frac{w_i}{\sum_{j \in S} w_j}.$$

Pessimistic weighted Shapley rules are introduced in Lorenzo and Lorenzo-Freire (2009). Each agent i has a weight $w_i > 0$. The sharing function ϱ is defined through such weights as follows. For each weight system $w = (w_i)_{i \in N}$, the pessimistic weighted Shapley rule $f^{\varrho^{pw}}$ is the Kruskal sharing rule associated with the obligation function o where for each $S \subset N$ and each $i \in S$,

$$o_i(S) = \sum_{\pi \in \Pi(S \setminus \{i\})} \prod_{j=1}^{s-1} \frac{w_{\pi^{-1}(j)}}{\sum_{k=1}^j w_{\pi^{-1}(k)} + w_i}.$$

Rules defined through Boruvka's algorithm

Borůvka (1926) provides an algorithm for computing an *mt*. Bergantiños and Vidal-Puga (2011) introduce a rule based on Boruvka's algorithm. We provide an informal definition of Boruvka's algorithm and the rule associated with it. We refer the reader to Bergantiños and Vidal-Puga (2011) for a formal definition.

We start with an empty network. Besides, each agent is a single component. Then, sequentially, for each connected component, we add the cheapest arc joining this connected component with some agent outside this connected component but without introducing cycles. The cost of each arc selected by Boruvka's algorithm is divided among the agents following three principles. First, each agent only pays the arc selected by the component it belongs to. Second, all agents pay the same proportion of the arc selected by the component. Third, the proportion paid should be as large as possible. Bergantiños and Vidal-Puga (2011) prove that this rule coincides with the folk rule.

Rules defined through a cone-wise decomposition

Norde et al. (2004) prove that every *mcstp* can be written as a non-negative combination of the so called *elementary* (or *simple*) *mcstp*, in which the costs of the arcs are 0 or 1.

Formally, for each *mcstp* (N_0, C) , there exists a family $\{C^q\}_{q=1}^{m(C)}$ of cost matrices and a family $\{x^q\}_{q=1}^{m(C)}$ of non-negative real numbers satisfying three conditions:

1. $C = \sum_{q=1}^{m(C)} x^q C^q$.
2. For each $q \in \{1, \dots, m(C)\}$, there exists a network g^q such that $c_{ij}^q = 1$ if $(i, j) \in g^q$ and $c_{ij}^q = 0$ otherwise.
3. Let $q \in \{1, \dots, m(C)\}$ and $\{i, j, k, l\} \subset N_0$. If $c_{ij} \leq c_{kl}$, then $c_{ij}^q \leq c_{kl}^q$.

Assume we know how a rule R should share the cost in any elementary problem. Then, we can extend the rule R for elementary problems to any general *mcstp* by using the decomposition given by Norde et al. (2004) as follows:

$$R(N_0, C) = \sum_{q=1}^{m(C)} x^q R(N_0, C^q).$$

Several authors have followed this approach for defining rules or family of rules. We mention some of them.

Branzei et al. (2004) proved that the folk rule can be obtained in this way. Given an elementary problem (N_0, C^q) , agents in the same component as the source (and hence

connected to the source through a path of cost 0) pay 0. Agents in any other component equally divide the cost of connecting them to the source, which is 1. Formally,

$$F(N_0, C^q) = \begin{cases} \frac{1}{S(P(g^q), i)} & \text{if } 0 \notin S(P(g^q), i) \\ 0 & \text{otherwise.} \end{cases}$$

Bergantiños and Lorenzo-Freire (2008b) prove that optimistic weighted Shapley rules can also be obtained in this way by taking

$$f^{e^{ow}}(N_0, C^q) = \begin{cases} \frac{w_i}{\sum_{j \in S(P(g^q), i)} w_j} & \text{if } 0 \notin S(P(g^q), i) \\ 0 & \text{otherwise.} \end{cases}$$

Bogomolnaia and Moulin (2010) consider the following family of rules. Given an elementary problem (N_0, C^q) and agent $i \in N$, let δ_i denote the number of non-null edges in C^q containing agent i . For each $\lambda \in [0, +\infty)$,

$$R^\lambda(N_0, C^q) = \begin{cases} \frac{\lambda^{\delta_i}}{\sum_{j \in S(P(g^q), i)} \lambda^{\delta_j}} & \text{if } 0 \notin S(P(g^q), i) \\ 0 & \text{otherwise} \end{cases}$$

and for $\lambda = +\infty$

$$R^\lambda(N_0, C^q) = \begin{cases} \arg \max_{j \in S(P(g^q), i)} \delta_j & \text{if } 0 \notin S(P(g^q), i) \\ 0 & \text{otherwise.} \end{cases}$$

2.3 Cooperative games

We briefly review some concepts of cooperative games used in this paper. In some cases, we simply give an informal definition, the notation, and a reference where it is possible to find the formal definition.

A *cooperative game with transferable utility*, briefly a *TU game*, is a pair (N, v) where $v : 2^N \rightarrow \mathbb{R}$ satisfies that $v(\emptyset) = 0$.

We say that (N, v) is *concave* if, for all $S, T \subset N$ and $i \in N$ such that $S \subset T$ and $i \notin T$,

$$v(S \cup \{i\}) - v(S) \geq v(T \cup \{i\}) - v(T).$$

The *core* is defined as

$$\text{core}(N, v) = \left\{ x \in \mathbb{R}^N : \sum_{i \in N} x_i = v(N) \text{ and } \sum_{i \in S} x_i \leq v(S), \forall S \subset N \right\}.$$

The *Shapley value* (Shapley, 1953b), denoted as $Sh(N, v)$, is defined as the average of marginal contributions over all possible orders in which agents may appear. Namely,

for each $i \in N$,

$$Sh_i(N, v) = \frac{1}{|N|!} \sum_{\pi \in \Pi(N)} [v(Pre(i, \pi) \cup \{i\}) - v(Pre(i, \pi))].$$

An alternative to marginal contributions are the *reduced marginal contributions* (Vidal-Puga, 2004) defined as

$$s_i^\pi(v) = v_s(N \setminus Pre(i, \pi)) - v_s(N \setminus (Pre(i, \pi) \cup \{i\}))$$

where $s = (s_j^\pi(v))_{j \in Pre(i, \pi)}$ and $(N \setminus Pre(i, \pi), v_s)$ is the reduced game defined as

$$v_s(T) = \begin{cases} 0 & \text{if } T = \emptyset \\ \max_{S \subseteq Pre(i, \pi)} \{v(T \cup S) - \sum_{j \in S} s_j\} & \text{otherwise} \end{cases}$$

for all $T \subseteq N \setminus Pre(i, \pi)$.

Shapley (1953a) introduced the family of *weighted Shapley values* for TU games. Each agent $i \in N$ has positive weight w_i . These weights are the proportions in which the players share in unanimity games. Kalai and Samet (1987) further studied this family. We denote by $Sh^w(N, v)$ the weighted Shapley value associated with the weight system $w = (w_i)_{i \in N}$. For each $i \in N$,

$$Sh_i^w(N, v) = \sum_{\pi \in \Pi(N)} p_w(\pi) [v(Pre(\pi, i) \cup \{i\}) - v(Pre(\pi, i))]$$

where $p_w(\pi) = \prod_{j=1}^{|N|} \frac{w_{\pi(j)}}{\sum_{k=1}^j w_{\pi(k)}}$.

Owen (1977) introduced a value for TU games with a group structure. Agents are partitioned into different groups. We denote by P such partition. We should divide $v(N)$ among the agents taking into account the partition P . Owen (1977) proved that his value generalizes the Shapley value. We call it the *Owen value* and denote it as $Ow(N, v, P)$.

We say that a permutation $\pi \in \Pi_N$ is admissible with respect to P if given $i, i' \in P^k \in P$ and $j \in N$ with $\pi(i) < \pi(j) < \pi(i')$, then $j \in P^k$. We denote by Π^G the set of all permutations over N admissible with respect to P . Given (N, v, P) and $i \in P^k \in P$,

$$Ow_i(N, v, G) = \frac{1}{|\Pi^G|} \sum_{\pi \in \Pi^G} [v(Pre(i, \pi) \cup \{i\}) - v(Pre(i, \pi))].$$

Weber (1988) introduced the *marginalistic values* of a cooperative game as generalizations of the Shapley value. Weber considers that agent i 's marginal contribution to a coalition S is weighted by an exogenously specified factor. Let p^i be a weight scheme for agent $i \in N$, where negative weights are also allowed. Formally, $p^i \in \mathbb{R}^{\{|S: S \subset N \setminus \{i\}|\}}$ and

$\sum_{S \subset N \setminus \{i\}} p^i(S) = 1$. We define the marginalistic value f^p associated with a collection of weight schemes $p = \{p^i\}_{i \in N}$ as follows. Given the TU game (N, v) and $i \in N$,

$$f_i^p(N, v) = \sum_{S \subset N \setminus \{i\}} p^i(S) (v(S \cup \{i\}) - v(S)).$$

3 The private game

Bird (1976) associated with each $mcstp(N_0, C)$ a TU game (N, v_C^p) where the cost of each coalition S is computed under the assumption that agents in $N \setminus S$ are not available. We call this game private because the nodes in $N \setminus S$ belong to these agents and hence their participation is needed in order to use their nodes.

Formally, the TU game (N, v_C^p) associated with each $mcstp(N_0, C)$ is defined as follows. For each coalition $S \subseteq N$,

$$v_C^p(S) = m(S_0, C). \quad (1)$$

When no confusion arises, we write v^p instead of v_C^p .

We compute v^p in Example 2.1.

S	$\{1\}$	$\{2\}$	$\{3\}$	$\{1, 2\}$	$\{1, 3\}$	$\{2, 3\}$	N
$v^p(S)$	12	15	20	16	18	23	22

Hence, $v^p(\{2, 3\})$ is computed using only nodes 2 and 3. Thus, the minimal tree in the problem $(\{2, 3\}_0, C)$ is $\{(0, 3), (2, 3)\}$.

Kobayashi and Okamoto (2014) provide sufficient and necessary conditions for v^p to be a concave game. Moreover, when the costs are restricted to two possible values, low and high (as in elementary problems), then v^p is concave if and only if the cycles formed by arcs of low cost are either adjacent to the source or pairwise adjacent. This condition can be verified in polynomial time.

Bird (1976) proved that for each $mcstp(N_0, C)$, the core of v^p is nonempty. Later on, the core was studied by other authors. We mention some other results about the core.

Theorem 3.1 1. (Bird, 1976) For each $mcstp(N_0, C)$, the Bird's rule $B(N_0, C)$ belongs to the core of v^p .

2. (Feltkamp et al., 1994) For each $mcstp(N_0, C)$, the folk rule $F(N_0, C)$ belongs to the core of v^p .

3. (Dutta and Kar, 2004) For each $mcstp(N_0, C)$, the Dutta-Kar's rule $DK(N_0, C)$ belongs to the core of v^p .

4. (Tijs et al., 2006a) For each $mcstp (N_0, C)$, each obligation rule $f^{e^o} (N_0, C)$ belongs to the core of v^p .
5. (Bogomolnaia and Moulin, 2010) For each $mcstp (N_0, C)$ and each $\lambda \in [0, +\infty)$, $R^\lambda (N_0, C)$ belongs to the core of v^p .
6. (Trudeau and Vidal-Puga, 2017) For each $mcstp (N_0, C)$, the core of v^p is the convex hull of the reduced marginal contributions vectors.

Since optimistic weighted Shapley rules are obligation rules (Bergantiños and Lorenzo-Freire, 2008a,b) and pessimistic weighted Shapley rules are also obligation rules (Lorenzo and Lorenzo-Freire, 2009), both belong to the core of v^p .

Moreover, Moretti et al. (2002) study some monotonicity properties of the core of v^p .

Next result applies to $mcstp$ with a unique mt :

Theorem 3.2 (Chun and Lee, 2012) *The unique sequential contributions rule that selects a core allocation in the private game v^p for each $mcstp$ with a unique mt is the Bird's rule.*

Next result applies to elementary $mcstp$:

Theorem 3.3 (Kuipers, 1993)

1. For each elementary $mcstp$, there exists an associated concave elementary graph game, which has the same core as v^p .
2. For each elementary $mcstp$, its extreme core allocations are marginal allocation vectors of the game v^p .

We now mention, briefly, some single values for $mcstp$ that has been defined through the game v^p .

Granot and Huberman (1981, 1984) study the core and the nucleolus of v^p . They prove that the core and the nucleolus can be obtained as a Cartesian product of the core and the nucleolus of some subproblems. They also provide efficient algorithms for the computation of the core and the nucleolus.

Faigle et al. (1998) prove that computing the nucleolus is NP -hard.

Kar (2002) defines a rule as the Shapley value of v^p . Namely, for each $mcstp (N_0, C)$, he considers $Sh(N, v^p)$. He obtains an axiomatic characterization of this value. Ando (2012) proves that computing this Shapley value is NP -hard, even for elementary games.

Trudeau and Vidal-Puga (2017, 2020) study the permutation-weighted average of extreme points of the core in elementary cost matrices. Moreover, Trudeau and Vidal-Puga (2020) provide a necessary condition for the coincidence of these three values, i.e., the nucleolus, the Shapley value, and the permutation-weighted average of extreme points of the core of v^p .

4 The irreducible game

We associate with each $mcstp (N_0, C)$ a TU game (N, v_C^i) defined as the private game associated with the irreducible form (N_0, C^*) . Thus, for each coalition $S \subseteq N$,

$$v_C^i(S) = m(S_0, C^*). \quad (2)$$

This game was already considered in Bird (1976). When no confusion arises, we write v^i instead of v_C^i .

We compute v^i in Example 2.1.

S	$\{1\}$	$\{2\}$	$\{3\}$	$\{1, 2\}$	$\{1, 3\}$	$\{2, 3\}$	N
$v^i(S)$	12	12	12	16	18	18	22

Now, $v^i(\{2, 3\})$ is also computed using only the nodes 2 and 3, but considering C^* instead of C . Thus, the minimal tree in problem $(\{2, 3\}_0, C^*)$ is $\{(0, 3), (2, 3)\}$, but the cost is 18 (instead of 23).

Bird (1976) proved that for each $mcstp (N_0, C)$ the core of v^i (usually called the *irreducible core*) is nonempty and it is a subset of the core of v^p . Later on, the core of v^i was studied by other authors.

We mention some other results about the irreducible core.

Theorem 4.1 1. (Bird, 1976) For each $mcstp (N_0, C)$, the irreducible core is the convex combination of the set of allocations induced by Prim's algorithm.

2. (Aarts and Driessen, 1993) For each $mcstp (N_0, C)$, v^i is concave.

3. (Bird, 1976) For each $mcstp (N_0, C)$, the Bird's rule $B(N_0, C)$ belongs to the core of v^i .

4. (Feltkamp et al., 1994) For each $mcstp (N_0, C)$, the folk rule $F(N_0, C)$ belongs to the core of v^i .

5. (Tijs et al., 2006a) For each $mcstp(N_0, C)$, each obligation rule $f^{e^o}(N_0, C)$ belongs to the core of v^i .
6. (Tijs et al., 2006b) The core of v^i is the largest solution which is efficient, non-negative, upper-bounded by the stand-alone costs, and cone-wise positive linear.
7. (Bergantiños and Vidal-Puga, 2015) For each $mcstp(N_0, C)$, the core of v^i coincides with the set of allocation induced by the set of all monotonic rules over the cost matrix and the set of agents.

Since optimistic weighted Shapley rules are obligation rules (Bergantiños and Lorenzo-Freire, 2008a,b), and pessimistic weighted Shapley rules are also obligation rules (Lorenzo and Lorenzo-Freire, 2009), both belong to the core of v^i .

We now consider the Shapley value of v^i . We also consider other values of TU closely related with the Shapley value.

Bergantiños and Vidal-Puga (2007a) define a rule as the Shapley value of v^i . Namely, for each $mcstp(N_0, C)$, they consider $Sh(N, v^i)$.

- Theorem 4.2**
1. (Bergantiños and Vidal-Puga, 2007a) For each $mcstp(N_0, C)$, the folk rule of (N_0, C) coincides with $Sh(N, v^i)$.
 2. (Bergantiños and Vidal-Puga, 2007a) For each $mcstp(N_0, C)$, the Bird's rule of (N_0, C^*) coincides with $Sh(N, v^i)$.
 3. (Lorenzo and Lorenzo-Freire, 2009) The family of pessimistic weighted Shapley rules coincides with the family of weighted Shapley values of v^i .
 4. (Bergantiños and Kar, 2010) For each $mcstp(N_0, C)$, the set of obligation rules is a subset of the set of marginalistic values of v^i .

A comparative of the Shapley value in the irreducible game (folk solution) and in the private game (Kar solution) can be found in Trudeau (2014b). Ando and Kato (2010) prove that the Shapley value in the irreducible game, as well as the egalitarian solution and the nucleolus, can be computed in time $O(|N|^2)$. For irreducible cost matrices, Trudeau and Vidal-Puga (2020) show that the the Shapley value, the nucleolus and the permutation-weighted average of extreme points of the core of v^i coincide.

Moreover, Bergantiños and Gómez-Rúa (2010, 2015) study the rule given by the Owen value of v^i .

5 The optimistic game

As an alternative to Bird's approach, Bergantiños and Vidal-Puga (2007b) associate with each $mcstp$ (N_0, C) a cooperative game (N, v_C^o) where the worth of each coalition S is computed assuming that agents in $N \setminus S$ are already connected. We call this game optimistic because agents in $N \setminus S$ can connect to the source through agents in $N \setminus S$ for free.

Let (N_0, C) be an $mcstp$, and $S, T \subset N$ with $S \cap T = \emptyset$. We define the associate $mcstp$ (S_0, C^T) assuming that agents in S have to be connected to the source, agents in T are already connected, and the agents in S can connect to the source through agents in T . Formally, $c_{ij}^T = c_{ij}$ for all $i, j \in S$ and $c_{0i}^T = \min_{j \in T_0} c_{ji}$ for all $i \in S$.

Bergantiños and Vidal-Puga (2007b) defined the TU game (N, v_C^o) associated with each $mcstp$ (N_0, C) . For each coalition $S \subseteq N$,

$$v_C^o(S) = m(S_0, C^{N \setminus S}). \quad (3)$$

When no confusion arises, we write v^o instead of v_C^o .

We compute v^o in Example 2.1.

S	$\{1\}$	$\{2\}$	$\{3\}$	$\{1, 2\}$	$\{1, 3\}$	$\{2, 3\}$	N
$v^o(S)$	4	4	6	10	10	10	22

Hence, $v^o(\{2, 3\})$ is computed assuming that agent 1 is already connected. Thus, agents 2 and 3 connect to the source through tree $\{(1, 2), (1, 3)\}$, which has a cost of 10.

We say that two $mcstp$ (N_0, C) and (N_0, C') are *tree-equivalent* if there exists a spanning tree t^* such that t^* is an mt for both (N_0, C) , and (N_0, C') and $c_{ij} = c'_{ij}$ for all $(i, j) \in t^*$.

In the next theorem we summarize some results obtained for v^o .

Theorem 5.1 1. (Bergantiños and Vidal-Puga, 2007b) If (N_0, C^*) is irreducible, then v^p and v^o are dual, i.e.,

$$v^p(S) + v^o(N \setminus S) = m(N_0, C)$$

for all $S \subset N$.

2. (Bergantiños and Vidal-Puga, 2007b) If (N_0, C) and (N_0, C') are tree-equivalent, then $v_C^o = v_{C'}^o$.
3. (Bergantiños and Vidal-Puga, 2007b) The optimistic game associated to any $mcstp$ (N, C) coincides with the optimistic game associated to its irreducible form (N, C^*) , i.e., $v_C^o = v_{C^*}^o$.

In the next theorem, we summarize some results obtained for the Shapley value (and other related values) of v^o .

Theorem 5.2 1. *Bergantiños and Vidal-Puga (2007b)* For all mcstp (N_0, C) ,

$$Sh(N, v_C^o) = Sh(N, v_C^i) = Sh(N, v_{C^*}^o).$$

2. *(Bergantiños and Lorenzo-Freire, 2008b)* The family of optimistic weighted Shapley rules coincide with the family of weighted Shapley values of v^o .

Since $Sh(N, v^o) = Sh(N, v^i)$, and the folk rule coincides with $Sh(N, v^i)$, the Shapley value of v^o is just another way for obtaining the folk rule.

The family of optimistic weighted Shapley rules is studied from an axiomatic point of view in Bergantiños and Lorenzo-Freire (2008a). Moreover, Gómez-Rúa and Vidal-Puga (2017) prove that a version of such an optimistic weighted Shapley rule is immune to manipulation by merging or splitting of nodes in a slightly more general model.

6 The public game

A natural alternative to the private case is to assume that there are no property rights on nodes and agents in S can use, paying their cost, the nodes of their neighbors in $N \setminus S$ to connect to the source. This approach was first explicitly studied by Bogomolnaia and Moulin (2010).

We compute v^u in Example 2.1.

S	$\{1\}$	$\{2\}$	$\{3\}$	$\{1, 2\}$	$\{1, 3\}$	$\{2, 3\}$	N
$v^u(S)$	12	15	18	16	18	22	22

Now, $v^u(\{2, 3\})$ is computed assuming that agent 1 is available. Thus, agents 2 and 3 connect to the source through tree $\{(0, 1), (1, 2), (1, 3)\}$, which has a cost of 22.

The public game has not received much attention in the literature, and it has been limited to the contrast with the private game (Trudeau, 2013; Trudeau and Vidal-Puga, 2017, 2019). A possible reason for this lack of attention is that the private game is more tractable. Notice, for example, that $v^u(S) = \min_{S \subseteq T} v^p(T)$, i.e., it requires much more effort to compute $v^u(S)$. Moreover, the core allocations of the public game coincide with the core allocations of the private game with non-negative cost shares, as first noted by Bogomolnaia and Moulin (2010) and formally proved by Trudeau and Vidal-Puga (2017):

Theorem 6.1 *(Trudeau and Vidal-Puga, 2017)* $core(N, v^u) = core(N, v^p) \cap \mathbb{R}_+^N$.

Additionally, the public game associated with the irreducible form of a *mcstp* coincides with the private game associated with this irreducible form. Hence, the irreducible game can be defined from either the private or the public approach.

As a consequence, most of the results for the private game also hold for the public game. For the sake of completeness, we replicate these results for the public game. The proof is an immediate consequence of Theorem 3.1 and the non-negativity of the rules mentioned in the respective item.

- Theorem 6.2**
1. For each *mcstp* (N_0, C) , the Bird's rule $B(N_0, C)$ belongs to the core of v^u .
 2. For each *mcstp* (N_0, C) , the folk rule $F(N_0, C)$ belongs to the core of v^u .
 3. For each *mcstp* (N_0, C) , the Dutta-Kar's rule $DK(N_0, C)$ belongs to the core of v^u .
 4. For each *mcstp* (N_0, C) , each obligation rule $f^{\circ}(N_0, C)$ belongs to the core of v^u .
 5. (Bogomolnaia and Moulin, 2010) For each *mcstp* (N_0, C) and each $\lambda \in [0, +\infty)$, $R^\lambda(N_0, C)$ belongs to the core of v^u .
 6. (Trudeau and Vidal-Puga, 2017) For each *mcstp* (N_0, C) , the core of v^u is the convex hull of the reduced marginal contributions vectors.

Next result applies to *mcstp* with a unique *mt* :

Theorem 6.3 *The unique sequential contributions rule that selects a core allocation in the public game v^u for each *mcstp* with a unique *mt* is the Bird's rule.*

Proof. Under Theorem 6.2(1), we know that the Bird rule is a sequential contribution rule that select a core allocation in the public game. Under Theorem 6.1, the core of v^u is a subset of the core of v^p . Hence, any sequential contribution rule that select a core allocation in the public game does so also in the private game. Under Theorem 3.2, such a rule coincides with the Bird's rule. ■

Next result applies to elementary *mcstp*:

Theorem 6.4 (Trudeau and Vidal-Puga, 2017) *For elementary *mcstp* problems, the folk solution is the permutation-weighted average of extreme core allocations of the game v^u .*

7 The cycle-complete game

The last alternative to be considered is to associate with each $mcstp (N_0, C)$ a TU game (N, v_C^c) defined as the private game associated with the cycle-complete network (N_0, C^{**}) . Thus, for each coalition $S \subseteq N$,

$$v_C^c(S) = v_{C^{**}}^i(S) = m(S_0, C^{**}). \quad (4)$$

As usual, we write v^c instead of v_C^c .

This approach was studied by Trudeau (2012).

We compute v^c in Example 2.1.

S	$\{1\}$	$\{2\}$	$\{3\}$	$\{1, 2\}$	$\{1, 3\}$	$\{2, 3\}$	N
$v^c(S)$	12	15	15	16	18	23	22

Now, $v^c(\{2, 3\})$ is again computed using only the nodes 2 and 3, but considering C^{**} . In this case, there are two minimal trees in problem $(\{2, 3\}_0, C^{**})$, which are $\{(0, 3), (2, 3)\}$ and $\{(0, 2), (2, 3)\}$, both with cost 23.

Theorem 7.1 (Trudeau, 2012) *The game (N, v^c) is concave.*

Theorem 7.1 is not tight in the sense that there are concave $mcstp$ which are not cycle-complete. However, this result is tight if we look only at elementary $mcstp$.

It is well-known that the Shapley value of a concave cost game belongs to its core. Moreover, it is clear that $core(N, v^c) \subseteq core(N, v^p)$. Hence, the Shapley value of (N, v^c) , which Trudeau (2012) calls *cycle-complete solution*, belongs to both cores.

Theorem 7.2 (Trudeau, 2012) *For each $mcstp (N_0, C)$, the cycle-complete solution belongs to the core of the game v^p .*

Next result applies to elementary $mcstp$:

Theorem 7.3 (Trudeau and Vidal-Puga, 2017) *For elementary problems, the cycle-complete solution is the permutation-weighted average of extreme core allocations of the game v^p .*

A comparative of the Shapley value in the cycle-complete game (cycle-complete solution) and in the irreducible game (folk solution) can be found in Trudeau (2014a).

8 Relation between cores

It is clear from their definition that the cost of the grand coalition in all the games coincide, i.e., $v^p(N) = v^i(N) = v^o(N) = v^u(N) = v^c(N) = C(N)$, whereas for each coalition $S \subset N$,

$$v^o(S) \leq v^i(S) \leq v^u(S) \leq v^p(S)$$

and

$$v^o(S) \leq v^i(S) \leq v^c(S) \leq v^p(S).$$

Notice that both $v^u(S)$ and $v^c(S)$ lie between $v^i(S)$ and $v^p(S)$. They are not related though.

As an implication, we have the following relations:

$$\text{core}(N, v^o) \subseteq \text{core}(N, v^i) \subseteq \text{core}(N, v^u) \subseteq \text{core}(N, v^p)$$

and

$$\text{core}(N, v^o) \subseteq \text{core}(N, v^i) \subseteq \text{core}(N, v^c) \subseteq \text{core}(N, v^p).$$

The core of v^o is, in general, empty. The rest of the cores are always nonempty. This implies that any stable cost allocation for v^i is stable in all the other games except v^o , and that we can always find such an allocation. As a counterpart, focusing on the core of v^i rules out other relevant properties for the private game, such as strict monotonicity and strict ranking (Trudeau, 2012).

9 Conclusions and future research

In this paper, we have reviewed the contribution of cooperative game theory to the problem of sharing the cost of *mcstp* between the agents. This contribution is, however, far from being closed, as there are numerous natural extensions, many of them deriving in balanced games, that have not been fully explored yet.

Some examples of extensions with nonempty core that have received some attention in the literature are the following:

- Minimum cost spanning tree problems where some agents are indifferent (Trudeau, 2014c), i.e., they can connect to the source (and get rewarded for it) if it helps others agents.
- Arborescences (Dutta and Mishra, 2012; Bahel and Trudeau, 2017), where the costs are not symmetric, i.e., $c_{ij} \neq c_{ji}$ in general.

- Minimum cost spanning tree problems where the costs are uncertain and represented by closed intervals (Moretti et al., 2011).
- Minimum cost spanning tree problems with multiple sources (Bergantiños and Navarro-Ramos, 2019b,a; Bergantiños and Lorenzo, 2020; Bergantiños et al., 2020) where agents want to be connected to several sources.
- Multi-period shorted path problems (Streekstra and Trudeau, 2020) generalize *mcstp* to several periods, so that the agents should receive from the source different amount of services in different periods.

Some examples of extensions with empty core are the following:

- Steiner tree problems (Megiddo, 1978), where agents can use some special (*Steiner*) nodes, if needed, to connect to the source. However, some special cases are always balanced (Skorin-Kapov, 1995), as for example when all Steiner nodes belong to an optimal tree (Skorin-Kapov and Skorin-Kapov, 2012).
- Multi-criteria minimum cost spanning tree games (Fernández et al., 2004), where the cost of the arcs are vectors instead of numbers. In this extended class of games, the *dominance core* (where inequalities apply to at least some dimension) is nonempty, whereas the *preference core* (where inequalities apply to all dimensions) may be empty.
- Minimum cost spanning tree problems with revenues (Bergantiños and Lorenzo, 2008; Estévez-Fernández and Reijnierse, 2014) are games where some agents have a limited budget, i.e., they connect if their assigned payment is not more than their connection revenue, or budget. These problems also generalize minimum cost spanning tree problems where some agents are indifferent.
- k -Hop minimum cost spanning tree problems (Bergantiños et al., 2012, 2014), where no agent can be more than k nodes away from the source.
- Directed acyclic graph games (Sziklai et al., 2016) arise from problems where some directions are unfeasible, so that the graph is directed, it has no cycles, and there always exists at least one path from each agent to the source. Moreover, some nodes are optional (Steiner nodes) and hence these problems also generalize Steiner tree problems.

- Minimum cost spanning tree problems with priced nodes (Trudeau and Vidal-Puga, 2017) generalize Steiner tree problems in the sense that each Steiner node has assigned a price, so that players should pay the price of the nodes they use.

In the other direction, some limited results have been obtained for some relevant subclasses of *mcstp*, as for example information graph games, which are characterized by elementary *mcstp*. Kuipers (1993) studies the core and Núñez and Vidal-Puga (2020) study the stable sets (von Neumann and Morgenstern, 1944) of these games. Since stable sets may exist for nonbalanced games, this research is also a promising open field of study in games where the core is empty.

References

- Aarts, H. (1994). *Minimum cost spanning tree games and set games*. PhD thesis, University of Twente.
- Aarts, H. and Driessen, T. (1993). The irreducible core of a minimum cost spanning tree game. *Methods and Models of Operations Research*, 38:163–174.
- Ando, K. (2012). Computation of the Shapley value of minimum cost spanning tree games: #P-hardness and polynomial cases. *Japan Journal of Industrial and Applied Mathematics*, 29(3):385–400.
- Ando, K. and Kato, S. (2010). Reduction of ultrametric minimum cost spanning tree games to cost allocation games on rooted trees. *Journal of the Operations Research Society of Japan*, 53(1):62–68.
- Aumann, R. J. and Maschler, M. (1985). Game theoretic analysis of a bankruptcy problem from the Talmud. *Journal of Economic Theory*, 36:195–213.
- Bahel, E. and Trudeau, C. (2017). Minimum incoming cost rules for arborescences. *Social Choice and Welfare*, 49(2):287–314.
- Bergantiños, G., Chun, Y., Lee, E., and Lorenzo, L. (2020). The folk rule for minimum cost spanning tree problems with multiple sources. *Mimeo, Repec*.
- Bergantiños, G. and Gómez-Rúa, M. (2010). Minimum cost spanning tree problems with groups. *Economic Theory*, 43(2):227–262.

- Bergantiños, G. and Gómez-Rúa, M. (2015). An axiomatic approach in minimum cost spanning tree problems with groups. *Annals of Operations Research*, 225(1):45–63.
- Bergantiños, G., Gómez-Rúa, M., Llorca, N., Pulido, M., and Sánchez-Soriano, J. (2012). A cost allocation rule for k-hop minimum cost spanning tree problems. *Operations Research Letters*, 40(1):52–55.
- Bergantiños, G., Gómez-Rúa, M., Llorca, N., Pulido, M., and Sánchez-Soriano, J. (2014). A new rule for source connection problems. *European Journal of Operational Research*, 234(3):780–788.
- Bergantiños, G. and Kar, A. (2010). On obligation rules for minimum cost spanning tree problems. *Games and Economic Behavior*, 69(2):224–237.
- Bergantiños, G. and Lorenzo, L. (2004). A non-cooperative approach to the cost spanning tree problem. *Mathematical Methods of Operations Research*, 59(3):393–403.
- Bergantiños, G. and Lorenzo, L. (2005). Optimal equilibria in the non-cooperative game associated with cost spanning tree problems. *Annals of Operations Research*, 137(1):101–115.
- Bergantiños, G. and Lorenzo, L. (2008). Non cooperative cost spanning tree problems with budget restrictions. *Naval Research Logistics*, 55(8):747–757.
- Bergantiños, G. and Lorenzo, L. (2020). Cost additive rules in minimum cost spanning tree problems with multiple sources. *Annals of Operations Research*, forthcoming.
- Bergantiños, G., Lorenzo, L., and Lorenzo-Freire, S. (2010). The family of cost monotonic and cost additive rules in minimum cost spanning tree problems. *Social Choice and Welfare*, 34(4):695–710.
- Bergantiños, G., Lorenzo, L., and Lorenzo-Freire, S. (2011). A generalization of obligation rules for minimum cost spanning tree problems. *European Journal of Operational Research*, 211(1):122–129.
- Bergantiños, G. and Lorenzo-Freire, S. (2008a). A characterization of optimistic weighted Shapley rules in minimum cost spanning tree problems. *Economic Theory*, 35(3):523–538.
- Bergantiños, G. and Lorenzo-Freire, S. (2008b). “Optimistic” weighted Shapley rules in minimum cost spanning tree problems. *European Journal of Operational Research*, 185(1):289–298.

- Bergantiños, G. and Moreno-Tertero, J. D. (2015). The axiomatic approach to the problem of sharing the revenue from museum passes. *Games and Economic Behavior*, 89:78–92.
- Bergantiños, G. and Moreno-Tertero, J. D. (2020). Sharing the revenues from broadcasting sport events. *Management Science*, 66(6):2417–2431.
- Bergantiños, G. and Navarro-Ramos, A. (2019a). A characterization of the folk rule for multi-source minimal cost spanning tree problems. *Operations Research Letters*, 47:366–370.
- Bergantiños, G. and Navarro-Ramos, A. (2019b). The folk rule through a painting procedure for minimum cost spanning tree problems with multiple sources. *Mathematical Social Sciences*, 99:43–48.
- Bergantiños, G. and Vidal-Puga, J. (2007a). A fair rule in minimum cost spanning tree problems. *Journal of Economic Theory*, 137(1):326–352.
- Bergantiños, G. and Vidal-Puga, J. (2007b). The optimistic TU game in minimum cost spanning tree problems. *International Journal of Game Theory*, 36(2):223–239.
- Bergantiños, G. and Vidal-Puga, J. (2009). Additivity in minimum cost spanning tree problems. *Journal of Mathematical Economics*, 45(1-2):38–42.
- Bergantiños, G. and Vidal-Puga, J. (2010). Realizing fair outcomes in minimum cost spanning tree problems through non-cooperative mechanisms. *European Journal of Operational Research*, 201(3):811–820.
- Bergantiños, G. and Vidal-Puga, J. (2011). The folk solution and Boruvka’s algorithm in minimum cost spanning tree problems. *Discrete Applied Mathematics*, 159(12):1279–1283.
- Bergantiños, G. and Vidal-Puga, J. (2015). Characterization of monotonic rules in minimum cost spanning tree problems. *International Journal of Game Theory*, 44(4):835–868.
- Bird, C. (1976). On cost allocation for a spanning tree: a game theoretic approach. *Networks*, 6(4):335–350.
- Bogomolnaia, A. and Moulin, H. (2010). Sharing a minimal cost spanning tree: Beyond the folk solution. *Games and Economic Behavior*, 69(2):238–248.

- Borm, P., Hamers, H., and Hendrickx, R. (2001). Operations research games: a survey. *Top*, 9(2):139–216.
- Borůvka, O. (1926). O jistém problému minimálním (about a certain minimal problem). *Práce moravské přírodovědecké společnosti v Brně*, 3:37–58. In Czech.
- Branzei, R., Moretti, S., Norde, H., and Tijs, S. (2004). The P-value for cost sharing in minimum cost spanning tree situations. *Theory and Decision*, 56:47–61.
- Chun, Y. and Lee, J. (2012). Sequential contributions rules for minimum cost spanning tree problems. *Mathematical Social Sciences*, 64(2):136–143. Bargaining, Evolution and Networks: A Special Issue in Honor of Hans Haller.
- Ciftci, B. and Tijs, S. (2009). A vertex oriented approach to the equal remaining obligations rule for minimum cost spanning tree situations. *Top*, 17(2):440–453.
- Claus, A. and Kleitman, D. (1973). Cost allocation for a spanning tree. *Networks*, 3(4):289–304.
- Curiel, I. (1997). Minimum cost spanning tree games. In Curiel, I., editor, *Cooperative Game Theory and Applications: Cooperative Games Arising from Combinatorial Optimization Problems*, volume 16 of *Theory and Decision Library*, chapter 6, pages 129–148. Academic Publishers, Boston, MA.
- Dutta, B. and Kar, A. (2004). Cost monotonicity, consistency and minimum cost spanning tree games. *Games and Economic Behavior*, 48(2):223–248.
- Dutta, B. and Mishra, D. (2012). Minimum cost arborescences. *Games and Economic Behavior*, 74(1):120–143.
- Estévez-Fernández, A. and Reijnierse, H. (2014). On the core of cost-revenue games: Minimum cost spanning tree games with revenues. *European Journal of Operational Research*, 237(2):606–616.
- Faigle, U., Kern, W., and Kuipers, J. (1998). Computing the nucleolus of min-cost spanning tree games is NP-hard. *International Journal of Game Theory*, 27(3):443–450.
- Feltkamp, V. (1995). *Cooperation in controlled network structures*. PhD thesis, Tilburg University, The Netherlands.

- Feltkamp, V., Tijs, S., and Muto, S. (1994). On the irreducible core and the equal remaining obligations rule of minimum cost spanning extension problems. Technical Report 106, CentER DP 1994, Tilburg University, The Netherlands.
- Feltkamp, V., Tijs, S., and Muto, S. (2000). Bird’s tree allocation revisited. In Patrone, García-Jurado, and Tijs, editors, *Game practice: Contributions from applied game theory*, pages 75–89. Kluwer.
- Fernández, F. R., Hinojosa, M. A., and Puerto, J. (2004). Multi-criteria minimum cost spanning tree games. *European Journal of Operational Research*, 158(2):399–408. Methodological Foundations of Multi-Criteria Decision Making.
- Giménez-Gómez, J.-M., Peris, J. E., and Subiza, B. (2020). An egalitarian approach for sharing the cost of a spanning tree. *PLoS ONE*, 15(7):e0236058–.
- Ginsburgh, V. and Zang, I. (2003). The museum pass game and its value. *Games and Economic Behavior*, 43:322–325.
- Gómez-Rúa, M. and Vidal-Puga, J. (2011). Merge-proofness in minimum cost spanning tree problems. *International Journal of Game Theory*, 40(2):309–329.
- Gómez-Rúa, M. and Vidal-Puga, J. (2017). A monotonic and merge-proof rule in minimum cost spanning tree situations. *Economic Theory*, 63:813–826.
- Granot, D. and Huberman, G. (1981). Minimum cost spanning tree games. *Mathematical Programming*, 21(1):1–18.
- Granot, D. and Huberman, G. (1984). On the core and nucleolus of minimum cost spanning tree problems. *Mathematical Programming*, 29(3):323–347.
- Hernández, P., Peris, J. E., and Vidal-Puga, J. (2020). A non-cooperative approach to the folk rule in minimum cost spanning tree problems. Mimeo, Universidade de Vigo.
- Kalai, E. and Samet, D. (1987). On weighted Shapley values. *International Journal of Game Theory*, 16(3):205–222.
- Kar, A. (2002). Axiomatization of the Shapley value on minimum cost spanning tree games. *Games and Economic Behavior*, 38(2):265–277.
- Kobayashi, M. and Okamoto, Y. (2014). Submodularity of minimum-cost spanning tree games. *Networks*, 63(3):231–238.

- Kruskal, J. B. (1956). On the shortest spanning subtree of a graph and the travelling salesman problem. *Proceedings of the American Mathematical Society*, 7:48–50.
- Kuipers, J. (1993). On the core of information graph games. *International Journal of Game Theory*, 21(4):339–350.
- Littlechild, S. and Owen, G. (1973). A simple expression for the Shapley value in a special case. *Management Science*, 20(3):370–372.
- Lorenzo, L. and Lorenzo-Freire, S. (2009). A characterization of Kruskal sharing rules for minimum cost spanning tree problems. *International Journal of Game Theory*, 38(1):107–126.
- Megiddo, N. (1978). Cost allocation for Steiner trees. *Networks*, 8(1):1–6.
- Moretti, S., Gök, S. Z. A., Branzei, R., and Tijs, S. (2011). Connection situations under uncertainty and cost monotonic solutions. *Computers and Operational Research*, 38(11):1638–1645.
- Moretti, S., Norde, H., Pham Do, K. H., and Tijs, S. (2002). Connection problems in mountains and monotonic allocation schemes. *Top*, 10(1):83–99.
- Norde, H. (2019). The degree and cost adjusted folk solution for minimum cost spanning tree games. *Games and Economic Behavior*, 113:734–742.
- Norde, H., Moretti, S., and Tijs, S. (2004). Minimum cost spanning tree games and population monotonic allocation schemes. *European Journal of Operational Research*, 154(1):84–97.
- Núñez, M. and Vidal-Puga, J. (2020). Stable cores in information graph games. Working paper, Universidade de Vigo.
- O’Neill, B. (1982). A problem of rights arbitration from the Talmud. *Mathematical Social Sciences*, 2(4):345–371.
- Owen, G. (1977). Values of games with a priori unions. In Henn, R. and Moeschlin, O., editors, *Mathematical Economics and Game Theory*, volume 141 of *Lecture Notes in Economics and Mathematical Systems*, pages 76–88. Springer-Verlag, Berlin.
- Prim, R. (1957). Shortest connection networks and some generalizations. *Bell Systems Technology Journal*, 36(6):1389–1401.

- Schmeidler, D. (1969). The nucleolus of a characteristic function game. *SIAM Journal of Applied Mathematics*, 17(6):1163–1170.
- Shapley, L. S. (1953a). *Additive and non-additive set functions*. PhD thesis, Princeton University.
- Shapley, L. S. (1953b). A value for n-person games. In Kuhn, H. and Tucker, A., editors, *Contributions to the theory of games*, volume II of *Annals of Mathematics Studies*, pages 307–317. Princeton University Press, Princeton NJ.
- Skorin-Kapov, D. (1995). On the core of the minimum cost steiner tree game in networks. *Annals of Operations Research*, 57:233–249.
- Skorin-Kapov, D. and Skorin-Kapov, J. (2012). A note on Steiner tree games. *Networks*, 59(2):215–225.
- Streekstra, L. and Trudeau, C. (2020). Stable source connection and assignment problems as multi-period shortest path problems. Discussion Papers on Business and Economics 7/2020, University of Southern Denmark.
- Subiza, B., Giménez-Gómez, J.-M., and Peris, J. E. (2016). Folk solution for simple minimum cost spanning tree problems. *Operations Research Letters*, 44(5):598–601.
- Sziklai, B., Fleiner, T., and Solymosi, T. (2016). On the core and nucleolus of directed acyclic graph games. *Mathematical Programming*, 163(1):243–271.
- Tijs, S., Branzei, R., Moretti, S., and Norde, H. (2006a). Obligation rules for minimum cost spanning tree situations and their monotonicity properties. *European Journal of Operational Research*, 175(1):121–134.
- Tijs, S., Moretti, S., Branzei, R., and Norde, H. (2006b). The Bird core for minimum cost spanning tree problems revisited: Monotonicity and additivity aspects. In Seeger, A., editor, *Recent Advances in Optimization*, volume 563 of *Lecture Notes in Economics and Mathematical Systems*, pages 305–322. Springer, Berlin Heidelberg.
- Trudeau, C. (2012). A new stable and more responsible cost sharing solution for mst problems. *Games and Economic Behavior*, 75(1):402–412.
- Trudeau, C. (2013). Characterizations of the Kar and folk solutions for minimum cost spanning tree problems. *International Game Theory Review*, 15(2):1340003–16.

- Trudeau, C. (2014a). Characterizations of the cycle-complete and folk solutions for minimum cost spanning tree problems. *Social Choice and Welfare*, 42(4):941–957.
- Trudeau, C. (2014b). Linking the Kar and folk solutions through a problem separation property. *International Journal of Game Theory*, 43:845–870.
- Trudeau, C. (2014c). Minimum cost spanning tree problems with indifferent agents. *Games and Economic Behavior*, 84:137–151.
- Trudeau, C. and Vidal-Puga, J. (2017). On the set of extreme core allocations for minimal cost spanning tree problems. *Journal of Economic Theory*, 169:425–452.
- Trudeau, C. and Vidal-Puga, J. (2019). The Shapley value in minimum cost spanning tree problems. In Algaba, E., Fragnelli, V., and Sánchez-Soriano, J., editors, *Chapters in Game Theory: The Shapley value*, chapter 24. CRC Press, Taylor & Francis Group.
- Trudeau, C. and Vidal-Puga, J. (2020). Clique games: A family of games with coincidence between the nucleolus and the shapley value. *Mathematical Social Sciences*, 103:8–14.
- Vidal-Puga, J. (2004). Bargaining with commitments. *International Journal of Game Theory*, 33(1):129–144.
- von Neumann, J. and Morgenstern, O. (1944). *Theory of games and economic behavior*. Princeton UP, first edition.
- Weber, R. (1988). Probabilistic values for games. In Roth, A. E., editor, *The Shapley value: Essays in honour of Lloyds S. Shapley*, pages 101–119. Cambridge University Press, Cambridge.